

TDOBCS2203

2 MP HDCVI IR BULLET CAMERA



FEATURES: NEW CUATRO SERIES

- 1/ 2.7" 2Megapixel CMOS
- Max 30fps@1080P
- High speed, long distance real-time transmission
- Day/Night(ICR), AWB, AGC, BLC, DWDR
- 3.6mm fixed lens
- Max. IR LEDs length 66FT, Smart IR
- IP67, DC12V

Specifications:

Model	TDOBCS2203
Camera	
Image Sensor	1/ 2.7" CMOS
Effective Pixels	1920(H)×1080(V), 2MP
Scanning System	Progressive
Electronic Shutter	PAL: 1/25~00000s NTSC:1/30~1/100000s
Min. Illumination	0.02Lux/F2.0, 0Lux IR on
S/N Ratio	More than 65db
IR Distance	Up to 20m (66ft)
IR On/Off Control	Auto/Manual
IR Leds	12
Lens	
Lens Type	Fixed Lens / Fixed Iris
Mount Type	Board-In
Focal Length	3.6mm
Max Aperture	F2.0
Angle of View	H:89.9° (59.4°)
Focus Control	N/A
Close Focus Distance	600mm (1800mm) 23.62" (70.87")
Pan / Tilt / Rotation	
Pan/Tilt/Rotation	Pan: 0°~360° Tilt: 0°~90° Rotation: 0°~360°
Video	
Resolution	1080P (1920×1080)
Frame Rate	25/30fps@1080P, 25/30/50/60fps@720P
Video Output	1-channel BNC high definition video output / CVBS video output (Can switch)

Day/Night	Auto (ICR) / Manual
OSD Menu	Multi-language
BLC Mode	BLC / HLC / DWDR
WDR	DWDR
Gain Control	AGC
Noise Reduction	2D
White Balance	Auto/Manual
Smart IR	Auto/Manual
Certifications	
Certifications	CE (EN55032, EN55024, EN50130-4) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
Interface	
Audio Interface	N/A
Electrical	
Power Supply	12 V DC±25%
Power Consumption	Max 3W (12 V DC, IR on)
Environmental	
Operating Conditions	-40°C ~ +60°C (-40°F ~ +140°F) / Less than 90% RH * Start up should be done at above -40°C (-40°F)
Storage Conditions	-40°C ~ +60°C (-40°F ~ +140°F) / Less than 90% RH
Ingress Protection & Vandal Resistance	IP67
Construction	
Casing	Aluminum
Dimensions	156.3mm×70mm×70mm (6.15"×2.76"×2.76")
Net Weight	0.30kg (0.66lb)
Gross Weight	0.37kg (0.82lb)

Accessories:



PFA134



PFA150

Corner Mount	Pole Mount
PFA134 + PFA151	PFA134 + PFA150
Junction Mount	
PFA134	

Dimensions:



